



OK

by Konstantin Grcic , 2014



Lamp providing direct light. Head in gloss varnished or chromed die-cast aluminium. Body in injection-stamped PA66+30%FV with cover in gloss varnished or chromed die-cast aluminium. Orientable head. The light fitting can be moved vertically by running the internal structure of the body on a steel cable tensioned between the ceiling and the floor (useful length 4000mm). Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs.



| | |
|-------------------------|---|
| Mounting | Pendant |
| Environment | Indoor |
| Weight | 2.9 Kg |
| Light sources available | 1 x Edge Lighting Technology 18W 1550lm 2700K CRI85 [i] Dimmable |
| Emergency | Without |
| Switching | Dimmable switch with Soft Touch technology. Adaptor on plug connector with interchangeable plugs. |
| Voltage | 100-240/24V |
| Power | 18W |
| Battery | No |
| Supply included | No |

| | |
|-------------|----------------------------|
| Cord Length | 4000 max mm |
| Materials | Aluminum, Polyamide, Steel |

| | |
|--------|--|
| Colors | <ul style="list-style-type: none"> F4640009 - White F4640030 - Black F4640019 - Yellow F4640057 - Chrome |
|--------|--|

| | |
|-------------|--|
| Certificate | |
|-------------|--|